

ISO 8217 2017 FUEL STANDARD

ISO 8217 2017 Fuel Standard for marine distillate fuels

REQUIREMENTS FOR MARINE DISTILLATE FUELS

Characteristic	Unit	Limit	Category ISO-F-						Test method(s) and references	
			DMX	DMA	DFA	DMZ	DFZ	DMB		DFB
Kinematic viscosity at 40 °C	mm ² /s ^a	Max	5,500	6,000		6,000		11,00	ISO 3104	
		Min	1,400	2,000		3,000		2,000		
Density at 15 °C	kg/m ³	Max	–	890,0		890,0		900,0	ISO 3675 or ISO 12185; see 6.1	
Cetane index	–	Min	45	40		40		35	ISO 4264	
Sulfur ^b	mass %	Max	1,00	1,00		1,00		1,50	ISO 8754 or ISO 14596, ASTM D4294; see 6.3	
Flash point	°C	Min	43,0	60,0		60,0		60,0	ISO 2719; see 6.4	
Hydrogen sulfide	mg/kg	Max	2,00	2,00		2,00		2,00	IP 570; see 6.5	
Acid number	mg KOH/g	Max	0,5	0,5		0,5		0,5	ASTM D664; see 6.6	
Total sediment by hot filtration	mass %	Max	–	–		–		0,10 ^c	ISO 10307-1; see 6.8	
Oxidation stability	g/m ³	Max	25	25		25		25 ^d	ISO 12205	
Fatty acid methyl ester (FAME) ^e	volume %	Max	–	–	7,0	–	7,0	–	7,0	ASTM D7963 or IP 579; see 6.10
Carbon residue – Micro method on the 10 % volume distillation residue	mass %	Max	0,30	0,30		0,30		–	ISO 10370	
Carbon residue – Micro method	mass %	Max	–	–		–		0,30	ISO 10370	
Cloud point ^f	winter	°C	Max	–16	report	report		–	ISO 3015; see 6.11	
	summer	°C	Max	–16	–	–		–		
Cold filter plugging point ^f	winter	°C	Max	–	report	report		–	IP 309 or IP 612; see 6.11	
	summer	°C	Max	–	–	–		–		
Pour point (upper) ^f	winter	°C	Max	–	–6	–6		0	ISO 3016; see 6.11	
	summer	°C	Max	–	0	0		6		
Appearance			Clear and Bright ^g						^e	see 6.12
Water	volume %	Max	–	–		–		0,30 ^c	ISO 3733	
Ash	mass %	Max	0,010	0,010		0,010		0,010	ISO 6245	
Lubricity, corrected wear scar diameter (WSD) at 60 °C ^h	µm	Max	520	520		520		520 ^d	ISO 12156-1	

a 1 mm²/s = 1 cSt.

b Notwithstanding the limits given, the purchaser shall define the maximum sulfur content in accordance with relevant statutory limitations. See Introduction.

c If the sample is not clear and bright, the total sediment by hot filtration and water tests shall be required, see 6.8 and 6.12.

d If the sample is not clear and bright, the test cannot be undertaken and therefore, compliance with this limit cannot be shown.

e See 5.1 and Annex A.

f Pour point cannot guarantee operability for all ships in all climates. The purchaser should confirm that the cold flow characteristics (pour point, cloud point, cold filter, plugging point) are suitable for the ship's design and intended voyage. See 6.11.

g If the sample is dyed and not transparent, then the water limit and test method as given in 6.12 shall apply.

h This requirement is applicable to fuels with a sulfur content below 500 mg/kg (0,050 mass %).

Permission to reproduce extracts of standards has been granted by Standard Norge. No other use of this material is permitted. Full standards may be obtained from the Standard Norge online shop, found at: <https://www.standard.no/en/webshop/>



Sea Trade LTD
physical bunker supplier
buy@seatrade-bunker.com

ISO 8217 2017 FUEL STANDARD

ISO 8217 2017 Fuel Standard for marine distillate fuels

REQUIREMENTS FOR MARINE DISTILLATE FUELS

Characteristic	Unit	Limit	Category ISO-F-										Test method reference	
			RMA	RMB	RMD	RME	RMG			RMK				
			10	30	80	180	180	380	500	700	380	500		700
Kinematic viscosity at 50 °C	mm ² /s ^a	Max	10,00	30,00	80,00	180,0	180,0	380,0	500,0	700,0	380,0	500,0	700,0	ISO 3104
Density at 15 °C	kg/m ³	Max	920,0	960,0	975,0	991,0	991,0			1010,0			ISO 3675 or ISO 12185; see 6.1	
CCAI	–	Max	850	860	860	860	870			870			see 6.2	
Sulfur ^b	mass %	Max	Statutory requirements										ISO 8754 or ISO 14596 or ASTM D4294; see 6.3	
Flash point	°C	Min	60,0	60,0	60,0	60,0	60,0			60,0			ISO 2719; see 6.4	
Hydrogen sulfide	mg/kg	Max	2,00	2,00	2,00	2,00	2,00			2,00			IP 570; see 6.5	
Acid number ^c	mg KOH/g	Max	2,5	2,5	2,5	2,5	2,5			2,5			ASTM D664; see 6.6	
Total sediment – Aged	mass %	Max	0,10	0,10	0,10	0,10	0,10			0,10			ISO 10307-2; see 6.9	
Carbon residue – Micro method	mass %	Max	2,50	10,00	14,00	15,00	18,00			20,00			ISO 10370	
Pour point (upper) ^d	winter	°C	Max	0	0	30	30	30			30			ISO 3016
	summer	°C	Max	6	6	30	30	30			30			
Water	volume %	Max	0,30	0,50	0,50	0,50	0,50			0,50			ISO 3733	
Ash	mass %	Max	0,040	0,070	0,070	0,070	0,100			0,150			ISO 6245	
Vanadium	mg/kg	Max	50	150	150	150	350			450			IP 501, IP 470 or ISO 14597; see 6.14	
Sodium	mg/kg	Max	50	100	100	50	100			100			IP 501, IP 470; see 6.15	
Aluminium plus silicon	mg/kg	Max	25	40	40	50	60			60			IP 501, IP 470 or ISO 10478; see 6.16	
Used lubricating oil (ULO): – Calcium and zinc; or – Calcium and phosphorus	mg/kg	–	Calcium > 30 and zinc > 15 or Calcium > 30 and phosphorus > 15										IP 501 or IP 470, IP 500; see 6.17	

a 1 mm²/s = 1 cSt.

b The purchaser shall define the maximum sulfur content in accordance with relevant statutory limitations. See Introduction.

c See Annex E.

d Purchasers should confirm that this pour point is suitable for the ship's intended area of operation.

Permission to reproduce extracts of standards has been granted by Standard Norge. No other use of this material is permitted. Full standards may be obtained from the Standard Norge online shop, found at: <https://www.standard.no/en/webshop/>



Sea Trade LTD
physical bunker supplier
buy@seatrade-bunker.com